SAFETY DATA SHEET

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

IDEAS ADDITIVES LLC
625 SOUTH MAIN STREET
LOMBARD, ILLINOIS 60148

I. PHYSICAL DATA

PRODUCT NAME: **A-158**
CHEMICAL FAMILY: Petroleum Hydrocarbon
FORMULA: Trade Secret

INFORMATION PHONE: 1-800-274-2010
EMERGENCY PHONE: 1-800-424-9300

II. HAZARDOUS IDENTIFICATION

NFPA RATING (SCALE 0-4) Health = 1 Flammability = 2 Reactivity = 0

EMERGENCY OVERVIEW: Do not ingest. Do not inhale dust. Use adequate ventilation and wash after handling.

GHS CLASSIFICATION:

Health	**Environmental**
Acute Toxicity: Cat. 4 Eye Irritation: Cat. 3 Skin Irritation: Cat. 2	Acute Aquatic Toxicity: Not established Chronic Aquatic Toxicity: Not established

GHS LABEL ELEMENTS:
Symbol(s):



Signal Word

Warning

Hazard Statements

Combustible. Material can release vapors that readily form flammable mixtures. Vapor accumulation could flash and/or explode if ignited. Material can accumulate static charges which may cause an ignition. May be harmful if swallowed. May cause skin and eye irritation.

Precautionary Statements

Wear protective gloves/protective clothing/eye protection/face protection IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or you feel unwell: Call a doctor/physician.

III. COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENT: Trade Secret
CAS NUMBER:

Distillates (petroleum) hydrotreated light napthenic	64742-53-6	<30%
Naphtha (petroleum) Hydrotreated Heavy	64742-48-9	>50%
Severely Hydrotreated Heavy Naphthenic Petroleum Oil	64742-52-5	10-30%

IV. FIRST AID MEASURES

EYE CONTACT: Wash eyes with water for at least 30 minutes. If irritation persists, get medical attention.
SKIN CONTACT: Wash affected area with soap and water for approximately 30 minutes
INHALATION: Remove exposed person to fresh air.
INGESTION: Do not induce vomiting. Get immediate medical attention.

V. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use carbon dioxide, foam, sand or sodium bicarbonate.
SPECIAL FIRE FIGHTING

PROCEDURES: Avoid breathing vapors or dusts. Use self-contained breathing apparatus with full face piece and protective clothing.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: None known.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED: Contain spill and transfer to suitable containers.

Stop leak if you can do it without risk.
Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. If material is too viscous for pumping scrape it up with shovels into suitable containers for recycle or disposal.
Large Spills: Dike far ahead of spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

VII. HANDLING AND STORAGE

STORAGE: Observe all federal, state and local regulations when storing or disposing of this substance. Keep away from incompatible substances.

Use good engineering practices to establish good ventilation. Avoid contact with skin, eyes and clothing. Wear suitable protective equipment to protect from contact. Avoid breathing mist or vapors. Wash skin thoroughly after handling. Store inn closed containers away from extreme heat, sparks, open flame or oxidizing materials.

VIII. EXPOSURE CONTROLS/ PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Naphtha (petroleum) Hydrotreated Heavy		Vapor	RCP-TWA	1200mg/m3
175ppm	Total Hydrocarbons			

SKIN PROTECTION: Wear appropriate protective gloves to prevent direct contact.

EYE PROTECTION: Wear safety goggles to prevent eye contact with substance.

RESPIRATORY PROTECTION: Under certain circumstances where airborne concentration are expected to exceed exposure limits, select a NIOSH/MSHA approved respirator based on actual or potential airborne concentrations and in accordance with the appropriate regulatory standards and/or industrial recommendations.

OTHER PROTECTIVE EQUIPMENT: Impervious apron if needed to avoid prolonged or repeated skin contact.

ENGINEERING CONTROLS: Good general ventilation and/or local exhaust ventilation at the point of generation is recommended.

PERSONAL PROTECTIVE EQUIPMENT (Pictograms):



IX. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT:	360°F			
VAPOR PRESSURE:	0.09 kPa (0.68 mm Hg) @ 20°C			
SOLUBILITY IN WATER:	Insoluble			
EVAPORATION RATE:	0.09			
APPEARANCE:	Amber Liquid			
ODOR:	Bland			
VAPOR DENSITY:	5.6 at 101 kPa			
FLASH POINT:	130°F			
FLAMMABLE LIMITS	**LOWER:**	0.7	**UPPER:**	5.3

X. STABILITY AND REACTIVITY

STABILITY: This product is stable at ambient temperatures.

CONDITIONS TO AVOID: Extreme heat or cold.

INCOMPATIBILITY: Avoid contact with strong acids and strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Exposure to high temperatures, such as those associated with fires causes product decomposition, resulting in the release of carbon monoxide, carbon dioxide, and other decomposition products.

HAZARDOUS POLYMERIZATION: Will not occur.

XI. TOXICOLOGY INFORMATION

POTENTIAL ACUTE HEALTH EFFECTS:

Eye: Eye contact may result in slight irritation and redness.

Skin: Short term contact with skin is unlikely to cause problems. Excessive or prolonged and repeated contact and poor hygiene conditions may result in dryness, dermatitis, erythema, oil acne, cracking and defatting of the skin.

Ingestion: May result in nausea or stomach discomfort.

Inhalation: Inhalation of vapors or mist may be irritating to respiratory passages. Target Organ for mineral oil mist is lungs. Prolonged exposure may result in dizziness and nausea.

POTENTIAL CHRONIC HEALTH EFFECTS:

Eyes: Vapor/aerosol concentrations above recommended exposure levels are irritating to eyes.

Respiratory: Vapor/aerosol concentrations above recommended exposure levels are irritating to respiratory system. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects including death.

Skin: Prolonged and /or repeated skin contact with low viscosity materials may defat the skin resulting in possibleirritation and dermatitis.

Target Organs: Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

XII. ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

ECOTOXICITY

Material-Not expected to be harmful to aquatic organisms.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Material- Expected to be readily biodegradable.

Hydrolysis:

Material-Transformation due to hydrolysis not expected to be significant.

Photolysis:

Material-Transformation due to photolysis not expected to be significant.

Atmospheric Oxidation:

Material-Expected to degrade rapidly in air.

OTHER ECOLOGICAL INFORMATION

VOC (EPA METHOD 24): 6.359 lbs/gal

XIII. DISPOSAL INFORMATION

WASTE DISPOSAL: Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state and local regulations.

XIV. TRANSPORTATION INFORMATION

DOT CLASSIFICATION

Proper Shipping Name:	PETROLEUM DISTILLATES, N.O.S.
Class:	3
UN Number:	1268
PG:	III

XV. REGULATORY INFORMATION

STATUS:
US (TSCA): Y
CANADA (DSL): Y
EUROPE (EINECS/ELINCS): Y
AUSTRALIA (AICS): Y
CHINA (IESCS): Y
JAPAN (ENCS): Y
SOUTH KOREA (KECI): Y

Y= All ingredients are on the inventory or exempt from listing
N= One or more non-exempt ingredients are not on the inventory

SECTION 302 EXTREMELY HAZARDOUS CHEMICALS:

Component	CAS#	% by Wt.
None		

SECTION 313 TOXIC CHEMICALS:

Component	CAS#	% by Wt.
None		

SARA TITLE III:
ACUTE (IMMEDIATE HEALTH HAZARD): Yes
CHRONIC (DELAYED HEALTH HAZARD): Yes
SUDDEN PRESSURE RELEASE: No
FIRE HAZARD: Yes
REACTIVE HAZARD: No

CERCLA (Comprehensive Environment Response, Compensation and Liability Act):

There is no calculable reportable quantity (RQ) for this product.

CLEAN WATER ACT: Under section 311 (b) (4) of this act, contamination of surface waters by petroleum products must be reported immediately to the National Response Center.

XVI. OTHER INFORMATION

TSCA (TOXIC SUBSTANCE CONTROL ACT) STATUS:
All components of this formula are included in the TSCA inventory. This product does not contain nor was manufactured with Class 1 or 11 ozone depleting chemicals, Section 611 of the Clean Air Act.

NFPA

HEALTH HAZARD
4-Deadly
3- Extreme Danger
2- Hazardous
1-Slightly Hazardous chemical change
0-Normal Material heated

FIRE HAZARD
Flash Points
4-Below 73°F
3-Below 100°F
2-Above 100°F, Not exceeding 200°F
1-Above 200°F
0-Will not burn

REACTIVITY
4-May detonate
3-Shock and heat may detonate
2-Violent
1-Unstable if
0-Stable

Table 3.8 Acute Toxicity

Acute toxicity	Cat. 1	Cat. 2	Cat. 3	Cat. 4	Category 5
Oral (mg/kg)	≤ 5	> 5 ≤ 50	> 50 ≤ 300	> 300 ≤ 2000	Criteria: ▪ Anticipated oral LD50 between 2000 and 5000 mg/kg; ▪ Indication of significant effect in humans;* ▪ Any mortality at class 4;* ▪ Significant clinical signs at class 4;* ▪ Indications from other studies.* *If assignment to more hazardous class is not warranted.
Dermal (mg/kg)	≤ 50	> 50 ≤ 200	> 200 ≤ 1000	> 1000 ≤ 2000	
Gases (ppm)	≤ 100	> 100 ≤ 500	> 500 ≤ 2500	> 2500 ≤ 5000	
Vapors (mg/l)	≤ 0.5	> 0.5 ≤ 2.0	> 2.0 ≤ 10	> 10 ≤ 20	
Dust & mists (mg/l)	≤ 0.05	> 0.05 ≤ 0.5	> 0.5 ≤ 1.0	> 1.0 ≤ 5	

Figure 4.11

ACUTE ORAL TOXICITY - Annex 1

	Category 1	Category 2	Category 3	Category 4	Category 5
LD_{50}	£ 5 mg/kg	> 5 < 50 mg/kg	³ 50 < 300 mg/kg	³ 300 < 2000 mg/kg	³ 2000 < 5000 mg/kg
Pictogram					No symbol
Signal word	Danger	Danger	Danger	Warning	Warning
Hazard statement	Fatal if swallowed	Fatal if swallowed	Toxic if swallowed	Harmful if swallowed	May be harmful if swallowed

Table 3.9 Skin Corrosion/Irritation

Skin Corrosion Category 1			Skin Irritation Category 2	Mild Skin Irritation Category 3
Destruction of dermal tissue: visible necrosis in at least one animal			Reversible adverse effects in dermal tissue Draize score: ≥ 2.3 < 4.0 or persistent inflammation	Reversible adverse effects in dermal tissue Draize score: ≥ 1.5 < 2.3
Subcategory 1A Exposure < 3 min. Observation < 1hr,	Subcategory 1B Exposure < 1hr. Observation < 14 days	Subcategory 1C Exposure < 4 hrs. Observation < 14 days		

Table 3.10 Eye Effects

Category 1 Serious eye damage	Category 2 Eye Irritation	
Irreversible damage 21 days after exposure Draize score: Corneal opacity ≥ 3 Iritis > 1.5	Reversible adverse effects on cornea, iris, conjunctiva Draize score: Corneal opacity ≥ 1 Iritis > 1 Redness ≥ 2 Chemosis ≥ 2	
	Irritant Subcategory 2A Reversible in 21 days	**Mild Irritant** Subcategory 2B Reversible in 7 days

Figure 4.9

GHS Pictograms and Hazard Classes

		
▪ Oxidizers	▪ Flammables ▪ Self Reactives ▪ Pyrophorics ▪ Self-Heating ▪ Emits Flammable Gas	▪ Explosives ▪ Self Reactives ▪ Organic Peroxides

	▪ Organic Peroxides	
		
▪ Acute toxicity (severe)	▪ Corrosives	▪ Gases Under Pressure
		
▪ Carcinogen ▪ Respiratory Sensitizer ▪ Reproductive Toxicity ▪ Target Organ Toxicity ▪ Mutagenicity ▪ Aspiration Toxicity	▪ Environmental Toxicity	▪ Irritant ▪ Dermal Sensitizer ▪ Acute toxicity (harmful) ▪ Narcotic Effects ▪ Respiratory Tract ▪ Irritation

Figure 4.10

Transport "Pictograms"		
		
Flammable Liquid Flammable Gas Flammable Aerosol	**Flammable solid Self-Reactive Substances**	**Pyrophorics (Spontaneously Combustible) Self-Heating Substances**
		
Substances, which in contact with water, emit flammable gases (Dangerous When Wet)	**Oxidizing Gases Oxidizing Liquids Oxidizing Solids**	**Explosive Divisions 1.1, 1.2, 1.3**

		
Explosive Division 1.4	**Explosive Division 1.5**	**Explosive Division 1.6**
		
Compressed Gases	**Acute Toxicity (Poison): Oral, Dermal, Inhalation**	**Corrosive**
		
Marine Pollutant	**Organic Peroxides**	

The information appearing in this document is based upon data obtained from raw material manufacturers and/or recognized technical sources. While this information is believed to be correct, IDEAS ADDITIVES LLC makes no representations as to its accuracy or sufficiency, usage or the hazards connected with the use of this material. Since this product may be applied under conditions unfamiliar to us or beyond our control, we claim no responsibility for the results of its use, and users are responsible for the verification of this information under their own operating conditions to determine whether the product is suitable for their particular purposes, and these users assume all risks of their use, handling, and disposal of the product. This information relates only to the product designated above and does not relate to its use in combination with any other process.

IDEAS ADDITIVES LLC
Revision Date: 10/16/2014